

## PRIMERO PRO DECK

### PRODUCT DESCRIPTION

Primero Pro-Deck is a professional grade, single component acrylic styrene polymer that is foot trafficable. It provides a seamless membrane that is flexible, very elastic, with high tensile strength. It is used to seal and waterproof interior and exterior concrete and metal surfaces, as well as fiber cement boards and other building materials.

### USES

Roof Decks, Concrete Slabs, Balconies, Firewalls, Parapet Walls, Old and New Roofs and Walls. Swimming Pools, Pre-primed Metals and Plant Boxes.

**COLORS:** Gray, Red & Green

### SIZES AVAILABLE

4kg, 25kg

### COVERAGE

4kg: 4-5 sq. meters (2 coats)

25kg: 25-28 sq. meters (2 coats)

1kg/sq. meter (2 coats)

### SURFACE PREPARATION

Make sure that surface is clean, dry, free from dirt, dust, oil and grease. Remove any fungus, efflorescence and loose particles or cement droppings. Surface must be sound with no evidence of segregation. Honeycombs must be hacked off and repaired with new plaster. For pre-painted walls, remove loose and flaking paint. Fill cracks with wall putty or fast curing cement if cracks are larger than 3mm.

### PRE-STRIPING

Pre-striping of cracks and joints: clean surface and remove old waterproofing that has been separated or unbundled. Cracks and expansion joints and areas where floor and wall meet should be filled by pre striping. Apply Primero Pro-Deck by brush by filling areas with joints and cracks 3" to 4" wide. Allow to dry and follow application instructions.



### APPLICATION

Apply 1 coat of Primero Pro-Deck horizontally. If paint is too thick, you may add up to 25% water to make paint into primer. Let it dry for 2 to 3 hours before recoating. Apply 1 coat vertically. Let it dry then apply second coat horizontally.

For areas with substantial movement such as roof decks with (AHU) or other machinery, apply with waterproofing fiber cloth. Apply 1 coat of Primero Pro Deck vertically. While still wet, lay fiber cloth into the paint. Use the brush to push fiber cloth firmly onto the paint, squeezing out air bubbles to eliminate creases. Let it dry for 2 to 3 hours then reapply second coat horizontally. You may apply a third coat vertically for better coverage and protection. It is recommended to apply 1 to 2 square meters at a time so that paint will not dry while applying fiber cloth. This will increase tensile strength. Allow 12 to 24 hours for foot traffic and 3 days for full cure.

For old walls, remove any loose or flaking paint. Sand surface to rid of efflorescence and apply wall putty or new cement plaster for areas with deep cracks. Let it dry and apply Primero Pro-Deck with the same instructions above.

### DRYING TIME

3 to 4 hours to recoat

12 to 24 hours hard dry

2 to 3 days for full cure