

BRONCO OIL WOOD STAIN

PRODUCT DESCRIPTION

Bronco Oil Wood Stain is a blend of premium colorants in a special resin to provide a long lasting, translucent appearance to wooden surfaces, which brings out the natural beauty in any kind of wood.

SUITABLE FOR

For enhancing wood grain on interior wood works and other surfaces such as cabinets, furniture, paneling, doors etc.

AVAILABLE SIZES

1 Liter

AVAILABLE COLOR

- Chestnut
- Red Mahogany
- DK Brown
- Cherry
- Walnut Brown
- Wheat Brown
- American Walnut

COVERAGE

10-12 sq. m. / liter

40-50 sq. m. / 4L

MIXING

Stir product well before using.

SURFACE PREPARATION

Sand surface until wood is smooth to touch and no rough edges remain, dust off surface completely then wipe with a clean dry rag. Fill all holes and cracks using wood filler. For previously finished wood in a poor condition, pour an ample amount of paint remover or stripping agent on the old rag. Wipe it on the old wood. Wait 5 - 10 minutes. Use the scraper to get off anything on the old wood. Always wipe off with an old rag after each scrape. Use (#180 grit) sandpaper to get rid of old stains or bumps on the wood. Apply stain until you achieve the desired color. Allow overnight drying of the stain before applying sanding sealer. Let the sanding sealer dry for 30 min to 1 hour.



Sand down with (#400 grit) sand paper or with a Mirka scrubbing pad (maroon) to remove minor imperfections and to create an even surface prior to top coating. Dust off with a clean dry cloth. Apply desired topcoat to provide a protective coating. Use Clear Gloss Lacquer for a glossy finish or Dead Flat Lacquer for a matte/flat finish. You can mix 50-50 ratio of the Clear Gloss and Dead Flat to achieve a satin finish.

APPLICATION

Method of Application:

Wiping or brushing. Wait 20-30 min. standby time for the stain to penetrate to the wood.

REDUCER

Paint Thinner

DRYTIME

Allow overnight drying before applying sanding sealer

SAFETY

Avoid inhaling vapor and use with adequate ventilation.

PRECAUTION

Product must be stored at room temperature. Do not store near heat, sparks or open flame. Exposure to heat may cause bursting. Use in a well-ventilated area. Avoid breathing vapors or spray must open windows and doors or use other means to insure fresh air entry during application. Should be applied during warm weather.

Use with adequate ventilation. May be fatal if swallowed. If swallowed induce vomiting contact a physician immediately.