

**PRIMERO MULTI-SEAL ELASTOMERIC WATERPROOFING****PRODUCT DESCRIPTION:**

Is a water-based premium sealant featuring outstanding flexibility and adhesion which is ready to use on wood, cement, hardiflex, plastics & properly primed metals.

**SUITABLE FOR:**

Seals nail holes, repairs roofs, seals gutters & downspouts, seal wall cracks, waterproof roof decks & firewalls.

**SURFACE PREPARATION:**

Make sure that surface is dry and free from dirt, dust and grease. REMOVE CEMENT DROPPINGS OR LOOSE, FLAKING PAINTS ON OLD WALLS MAY ALSO USE VACUUM TO REMOVE FINE DUST PARTICLES. Apply wall putty or cement plaster ON WALLS OR FLOORS WITH CRACKS. Make sure that NEW concrete has cured for at least four weeks. If not, apply Bronco Concrete Neutralizer or 2 coats of Bronco Concrete Primer Sealer.

**APPLICATION:**

Product is ready to use. No thinning is necessary. HOWEVER, you may add a maximum of 5% clean water to help smoothen brush strokes. PRE STRIPE MULTI SEAL ON CORNERS, EDGES AND AREAS WITH CRACKS. LET DRY. Apply FIRST COAT OF Pr1mero Multi-Seal vertically. Let dry for 1 to 2 hours. Apply second coat horizontally. It is best to apply two thin coats rather than one thick coating to aid in drying of sealant. For severe cracks on walls that are non-Structural, you may use Pr1mero Waterproofing Fiber Cloth immediately after the first coat while it is wet. Dab cloth with brush onto wet sealant. Smoothen the Fiber Cloth before it dries, pushing air bubbles out from fiber cloth. Let dry then Apply second coat or third coat if necessary.

**FOR WATERPROOFING OF ROOF DECKS, and BALCONIES**

Drying time will be longer in enclosed areas such as bathrooms and underground tanks. Make sure area is well-ventilated. APPLY third coat if area is subject to heavy load or if machines like air handling units, pumps or exhaust fans are near. Top at least 1-inch thick cement topping for balconies with heavy foot traffic.

**COVERAGE:**

Single coat 8-10 sq.m / 4kg. , 40-50 sq.m / 20kg  
Double coat 4-5 sq.m / 4kg. , 20-25 sq.m / 20kg

**APPLICATION TOOLS:**

Brush & Roller

**DRYING TIME:**

Touch dry : 15-30 minutes  
Hard dry : 12 hours

**SIZES AVAILABLE:**

200g & 600g round plastic  
4kg & 20kg

**BENEFITS:**

- Ready to use
- Easy to apply, brush application
- Water clean-up
- Water – based
- Flexible, elastic
- Excellent adhesion
- Long storage life
- U.V Resistant
- Non-Toxic