



Waterproof Cement Based Product

PYE PLASTA

Rendering plaster for interior and exterior use

DESCRIPTION

PYEPLASTA is a ready to use cement-based waterproof plaster for repairing and patching damaged or spalling off of old plastered surfaces. It can be used as a filling and levelling plaster for concrete surfaces, especially where the areas are subject to damp conditions. It can also be used to correct surface imperfections or unevenness prior to coating or painting.

SUITABLE FOR

- Filling and leveling masonry surfaces such as concrete, brickwork, blockwork and fairface concrete
- For repairing and patching old plaster or spalling off cement plaster and paintwork.

DIRECTIONS FOR USE

Surface preparation

Ensure surfaces are sound and clean. Remove all dust and loose materials. Coat nail heads with red oxide primer to prevent rust staining. Surfaces should be dampened to promote adhesion to the applied surfaces.

Mixing

Add 3 parts PYEPLASTA to 1 part water and mix thoroughly to a paste.

Note: Do not add water to extend the working time.

Application

Apply to wall, using a steel float trowel and press firmly into corners and edges. After initial filling, allow 1 hour for setting, then wet the surface with clean water. Apply the finishing coat render with a steel float to a fine smooth finish.

Do not fill deeper than 1 cm at a time. Build up in layers instead. Wait for at least 12 hours to dry before sanding down to a smooth surface.



Product Code: WAPL

PRODUCT CHARACTERISTICS

<i>Colour</i>	Light grey
<i>Adhesion</i>	Excellent adhesion properties to plaster, brick, stone, cement, concrete, and other masonry surfaces. However, do not use directly over wooden laths - use PYEPUTTYFILLA as a first coat.
<i>Drying time</i>	Allow at least 12 hours before sanding or painting.
<i>Coverage</i>	Approx 2 1/2 sq.m. at 3mm thickness per 10 kg pack.
<i>Filling thickness</i>	1 - 5 mm thick per treatment in 3 - 5 kg/sq.m.
<i>Shrinkage</i>	Will not shrink or crack when used in accordance with instructions. PYEPLASTA will take screws and nails without spalling or breaking away. However, it is not designed for use in areas subject to structural movement.
<i>Flexibility</i>	
<i>Sandability</i>	Can be sanded with medium to fine grade sandpaper.
<i>Cleaning</i>	Clean all equipment with water before plaster sets.

PACKING
1kg & 25kg

All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.