



PYETILE ADHESIVE

Ready mixed tile adhesive

DESCRIPTION

PYETILE ADHESIVE is a ready to use thin-bed adhesives for fixing ceramic tiles on most types of interior surfaces, including gypsum, plasterboard, wood, asbestos sheets etc. It can also be used for bonding insulating material such as foam polystyrene, glass or mineral wool.

SUITABLE FOR

PYETILE ADHESIVE is suitable for fixing ceramic tiles on walls and floors on suitable substrates such as concrete, cement render, plasterboard, wood, asbestos sheets etc.

DIRECTIONS FOR USE

Surfaces Preparation

The surface to be tiled must flat, sound and free from dust, grease or other foreign material.

Mixing

PYETILE ADHESIVE is supplied ready to use and no prior mixing is required.

Application

Apply PYETILE ADHESIVE with a notched trowel and the press the tiles firmly against the layer of adhesive. Well-formed ribs are essential for good adhesion. The thin-bed adhesive should not be greater than 3mm in thickness. Do not spread too large an area at a time. Tiles should be fixed within 20 minutes of application; otherwise surface drying before tiles are pressed home can result in poor adhesion. Working time will vary according to the porosity of the surface and atmospheric conditions. Ceramic tile are fixed dry and should not be pre-soaked. Press firmly in place with a slight twisting action. Allow spacing of about 2mm around every tile. (Spacer lugs may be used)

NEVER fix ceramic tiles with tight joints. For paper mounted mosaic tiles, the backing paper can be



Product Code: ADTI

removed 2 hours after application by damping it slightly. Excessive adhesive can be removed immediately with water after application. Grouting can be done when tiles are firmly set. We recommend using PYEGROUT.

PRODUCT CHARACTERISTICS

<i>Colour</i>	Light Grey
<i>Form</i>	Mastic
<i>pH</i>	8.5
<i>Flammability</i>	Non-flammable
<i>Binder</i>	High solids acrylic emulsion
<i>Adhesion</i>	Excellent wet and dry adhesion to a range of substrates.
<i>Coverage</i>	Varies with the condition of the surface to which the adhesive is applied and the type of trowel used. On average it is approx. 1 sq.m per kg.
<i>Safety</i>	Non-flammable Non-hazardous

PACKING

1.5kg, 5kg & 25kg.

All information contained within this brochure is only intended to give a fair description of the products and their capabilities under specific test conditions. However, it does not constitute an offer of warranty by the manufacturer nor a guarantee of its accuracy or completeness in describing the performance or suitability of the various products.