



PRIMERO PRO FLEXIBLE JOINT COMPOUND

PRODUCT DESCRIPTION

Primero Pro Flexible Joint Compound is a specially formulated flexible compound designed to minimize or eliminate joint cracks on hardiflex, gypsum boards, building boards, plywood and other building materials. It resists cracks caused by structural movement, expansion and contraction of building materials.

USES

For the filling, topping, skimming of joints on walls and ceilings on fiber cement boards, gypsum boards, plywood, cement and other building materials.

SIZES AVAILABLE

1.5 kg, 5 kg

COVERAGE

1 kg = 1 to 1.5 sq. meter per mm

ADVANTAGES

- Reduces cracks on wall and ceiling joints
- Excellent adhesion
- Fast drying
- Easy application
- Ready to use water-based formula
- Low odor
- Elastic when dry
- Low shrinkage

SURFACE PREPARATION

Surface must be clean, dry and free from dirt, dust and grease. Sand surface lightly. Inspect walls and ceilings to make sure that all of the screws are firmly embedded. Surfaces that are chalking and crumbling must be removed by sanding or scraping.

NOTE: Products is ready to use. However, if settling occurs, mix with a broad wooden stick.



APPLICATION FOR WALL AND CEILING JOINTS

Using a metal spreader, apply a thin layer of Primero Pro Flexible Joint Compound into the seam, pressing firmly to prevent air sockets. Spread compound along the seams to make a smooth surface. Let dry for 15 to 30 minutes, 1 hour if seams are deep. After first layer has dried, apply second coat along the seams in a long, smooth stroke. Make sure that edges are smooth and there are no lines or streaks on the compound. This is to minimize sanding and produces better painting results.

APPLICATION WITH MESH TAPE

Apply a thin layer of Primero Pro Flexible Joint Compound along the seams about 1.5" to 2" wide on each side of the board. Immediately apply 2" mesh tape and press down onto the joint. Make sure that mesh tape is flat on the wall. Let dry for 30 to 60 minutes. Apply second coat of flexible joint compound to cover the mesh tape. Smoothen edges to minimize sanding. Let dry for 3 to 4 hours. Sand lightly with grit 150 or 180 sandpaper. Then apply desired paint.

For overnight or long term storage, fill tub with clean water to cover compound. When ready to use, discard water, mix with mixing paddle until homogenous.

PRECAUTIONS

- Keep out of reach of children.
- Store in room temperature.
- Keep away from direct sunlight and sources of heat.
- Keep container closed when not in use.