



BRONCO CLEAR GLOSS LACQUER

PRODUCT DESCRIPTION:

A premium quality lacquer clear varnish for top coating interior woodwork. It is fast drying and imparts good film characteristics, such as high gloss, durability and toughness.

USES:

For interior sealed wood such as furnitures, fixtures, cabinets, doors, panels and picture frames, etc.

SIZES AVAILABLE:

1 Liter & 4 Liters

COVERAGE:

25-30 sq.m. / 4L per coat

5-7 sq.m. / liter per coat

DRY FILM THICKNESS:

1-1.5 mils/coat

NO. OF COATS:

1-2 coats

COLOR:

Clear Solution

METHOD OF APPLICATION:

Brush, Spray

REDUCER / CLEANER:

Bronco Premium Lacquer Thinner

DRYING TIME:

Touch Dry : 10 mins.

Recoat : 30 mins.

Hard Dry : 4 - 6 hours



SURFACE PREPARATION:

Stir Bronco Clear Gloss Lacquer well before using. Open grains and surface imperfections must be puttied with wood filler and sealed appropriately.

Ensure surface is clean and dry. Sand the wood surface along the grain with #220 - #240 grit to obtain a smooth and uniform surface. Remove all dust with a dry cloth. Apply desired wood stain if you prefer a different shade of wood. Please follow instructions on wood stain packaging. Use a good quality brush, or apply by using spray gun 1-2 coats of sanding sealer to seal open joints, edges and end grain on unfinished wood surfaces. Let dry at least 30 minutes, then sand with #360 - #400 grit sandpaper in the direction of the wood's grain. Remove all sanding dust with a clean dry rag. Apply with 1-2 coats Bronco Clear Gloss Lacquer.

Important Note:

Store in a cool, shaded area. Away from direct sunlight.

Use product in a well ventilated area