

## BRONCO ELASTOMERIC WATERPROOFING PAINT

### PRODUCT DESCRIPTION

Bronco Elastomeric Paint is a water-based elastic acrylic emulsion paint intended for interior and exterior masonry surfaces where a flexible and durable waterproof coating is required. It can bridge gaps and mask hairline cracks. It dries quickly into different surfaces with high resistance to ultra-violet rays.

### SUITABLE FOR

- Concrete walls
- Firewalls
- Interior and exterior walls
- Gypsum boards
- Cement boards and gutters

### AVAILABLE SIZES

4 Liters

### AVAILABLE COLORS

Sunny Day  
Sweet Corn  
White  
Baguio Green  
Vigan Red  
Black  
Crystal Blue  
Linen Cream  
Mocha Brown  
Peach  
Sunshine Yellow  
Terraza Orange  
Bitter Sweet  
Light Gray  
Terracotta

### SURFACE PREPARATION

Surface should be clean, dry and free from dirt, dust, oil and grease. Remove loose paint. Use paint scraper and sand with grit 120 - 180 sandpaper.



For old masonry, remove old loose paints with steel brush or metal palette. Sand down with grit 100 to 120 sandpaper to create an even surface. Apply filler or putty on small cracks or holes. Let dry overnight. Apply 2 to 3 coats of Bronco Elastomeric Paint and allow 2 hours before re-applying paint. Low temperature will affect drying time. Allow longer drying time before re-application. Clean tools and painting materials with water.

### MIXING

Stir thoroughly using a broad flat stirrer or mixing stick.

### APPLICATION

New surfaces should be treated with concrete neutralizer to reduce alkalinity. For best result, apply 1 to 2 coats of Bronco Concrete Primer Sealer to aid in adhesion and seal concrete pores. See package instructions for application. Apply 2 to 3 coats of Bronco Elastomeric Paint.

### COVERAGE

4 Liters: 20-25 sq. m (single coat)  
10-12 sq. m (double coat)  
16 Liters: 80-100 sq. m (single coat)  
40-50 sq. m (double coat)

### PRECAUTIONS

Do not take internally.  
Do not apply on wet surfaces.  
Keep out of reach of children.  
Store in room temperature, away from heat and direct sunlight.  
Keep container closed when not in use.