

BRONCO EPOXY FLOOR COAT SEALER

PRODUCT DESCRIPTION

Bronco Epoxy Floor Coat Sealer is a two-component epoxy sealer that is formulated as a primer to seal new or unpainted concrete floors prior to the application of epoxy floor coat. It promotes adhesion for the subsequent coats.

USES

Seal cement floors.

SIZES AVAILABLE

3 liters, set with catalyst

SURFACE PREPARATION

Surfaces to be painted must be thoroughly cleaned and free from oil, dust, dirt and grease. Old and loosely adhering, cracking and scaling paint must be scraped or sanded mechanically with grinder or sander using grit #40 or #60 sandpaper. Surface must be thoroughly clean and dry before application.

MIXING

Pour all contents of catalyst into Bronco Epoxy Floor Coat Sealer. Mix product well before using. Scrape bottom of can for settled pigments with a plastic or wood stirrer or stirring rod. Do not over-mix as it may introduce air bubbles into the paint.

DIRECTIONS FOR USE

Apply 1 to 2 coats of Epoxy Floor Coat Sealer depending on cement porosity and roughness. Let dry overnight. Apply 1 coat of Bronco Epoxy Floor Coat. Allow to overnight drying before reapplying second coat.



DRYING TIME

Touch dry in 4 to 5 hours. Allow to dry overnight before applying subsequent coat of epoxy sealer or epoxy floor coat.

Light foot traffic permissible after 72 hours. Full cure is achieved in 7 days for heavy traffic.

COVERAGE

30 TO 35 sq. meters/coat/gallon

PRECAUTIONS

Prepare mixture good for 6 to 8 hours work.
Mix product of what you can use in 4 hours.
Ratio is 3 parts resin, 1 part catalyst. Mixed product must be used within 4 to 6 hours.
Product will harden overnight.