



## BRONCO LACQUER SANDING SEALER

### PRODUCT DESCRIPTION:

Is formulated to penetrate well into wood substrates. It is fast drying and it provides a smooth finish for the clear topcoats.

### USES:

For interior & exterior sealed wood such as furniture, fixtures, cabinets, doors, panels, plywood, etc.

### SIZES AVAILABLE:

1 Liter & 4 Liters

### COVERAGE:

25-30 sq.m. / 4L per coat  
5-7 sq.m. / liter per coat

### DRY FILM THICKNESS:

1-1.5 mils/coat

### NO. OF COATS:

1-2 coats

### COLOR:

Milky white

### METHOD OF APPLICATION:

Brush, Spray

### REDUCER / CLEANER:

Bronco Premium Lacquer Thinner

### DRYING TIME:

Touch Dry : 3-5 mins.  
Recoat : 10 mins.  
Hard Dry : 30 mins.

### SUBSEQUENT COAT:

Bronco Clear Gloss Lacquer, Bronco Polyurethane Wood Varnish or equivalent top coat.



### SURFACE PREPARATION:

1. Mix or stir Bronco Sanding Sealer well before using. Sanding sealer should be milky white in appearance before application.
2. Ensure surface is clean and dry. Sand the wood surface along the grain with #150 or #220 grit to obtain a smooth and uniform surface. Remove all dust with a dry cloth.
3. Apply desired wood stain if you prefer a different shade of wood. Please follow instructions on wood stain packaging. Use a good quality brush, or apply by using spray gun. Apply 1-2 coats of sanding sealer to seal open joints, edges and end grain on unfinished wood surfaces.
4. Let dry at least 30 minutes, then sand with #320 or #400 grit sandpaper in the direction of the wood's grain. Remove all sanding dust with a clean dry rag. Apply preferred topcoat finish.

### IMPORTANT NOTE:

Store in a cool, shaded area. Away from direct sunlight.  
Use product in a well ventilated area