



BRONCO NGR PENETRATING STAIN

PRODUCT DESCRIPTION:

Bronco NGR Penetrating Stain is a blend of premium non-grain raising stain organic binders, non-bleeding dyes and solvents which when applied, accentuates the wood grain pattern. Its fast dry properties allow multiple coats in a day.

SUITABLE FOR:

For enhancing wood grain on interior wood works and other surfaces such as cabinets, furniture, paneling, doors etc.

APPLICATION:

Make sure that surfaces are clean, dry and smooth. Sand rough portions as it will absorb excessive stain and appearance will be uneven. Sand surface along the grain to achieve better results.

Stir product well before using. Use a medium-sized new brush. Test stain on a sample panel to check desired color. If a lighter tone is desired, thin with premium grade lacquer thinner. Make long, smooth light strokes, and try not to overlap the strokes. Once desired color is achieved, let dry for 30 minutes to 1 hour. Apply lacquer sanding sealer by spray or brush. Sand with grit 360 or 400. Apply desired topcoat (Clear Gloss Lacquer for gloss finish or Dead Flat Lacquer for a flat finish).

COVERAGE:

10 – 12 sq. m. per liter, or 40 – 50 sq. m. per 4 liters depending on type of wood and desired shade. Darker colors and light colored woods will consume more product.



SIZES AVAILABLE:

1 Liter

AVAILABLE COLORS:

- Candy Maple
- Walnut Brown
- Coco Brown
- Manor Brown
- Red Mahogany
- Acorn Brown
- Lt. Walnut
- Cherry

SAFETY:

Avoid inhaling vapor and use with adequate ventilation.

PRECAUTION:

Product must be stored at room temperature. Do not store near heat, sparks or open flame. Exposure to heat may cause bursting. Use in a well ventilated area. Avoid breathing vapors or spray must open windows and doors or use other means to insure fresh air entry during application. Should be applied during warm weather.

Use with adequate ventilation and avoid breathing its vapor. May be fatal if swallowed. If swallowed induce vomiting contact a physician immediately.