



BRONCO RUBBERIZED FLOOR COATING

PRODUCT DESCRIPTION:

A rubberized coating product that is one step, self-priming for use on concrete, metal and all general surfaces. It is fast drying and has excellent resistance to water, weather, oil, acid and other chemicals. It is formatted using a modified non-chlorinated formula that is non-toxic and ozone safe.

SUITABLE FOR:

- For exterior and interior concrete floors like offices, schools, sport courts, traffic marking paint, etc.
- Can be used as finish coat over properly primed metal.

APPLICATION:

Method of Application

Brush, Roller or Spray

Reducer / Cleaner

Bronco Floor Coat Reducer

% Reduction

Brush / Roller: 0 - 10%

Spray: 10 - 20%

Dry Time

Touch - 20 mins.

Hard - 2 - 4 hours

Recoat - 4 - 6 hours, minimum

Full Cure - 3 days

Recommended System

Undercoat - Bronco Rubberized Paint
reduced 10%. one coat

Topcoat - Bronco Rubberized Paint
Reduced 0 - 10%, 1 - 2 coats

SURFACE PREPARATION:

Preferred surface profile is semi-rough plaster finish and leveled. When concrete floor finish is smooth, mechanical grinding is recommended. Dust off with broom or best use vacuum cleaner to rid sand dust. Surface should be adequate dry, free from dirt and other contaminants prior to paint application.



COVERAGE:

20 sq. m. / 4L per coat

5 sq. m. / Liter per coat

SIZES AVAILABLE:

1 Liter & 4 Liters

AVAILABLE COLORS:

- Power Gray
- L.A. Yellow
- Mocha Brown
- Vigan Red
- Grass Green
- White
- Black
- River Blue

PRECAUTION:

Product must be stored at room temperature. Do not store near heat, sparks or open flame. Exposure to heat may cause bursting. Use in a well ventilated area. Avoid breathing vapors or spray must open windows and doors or use other means to insure fresh air entry during application. Should be applied during warm weather.

Use with adequate ventilation and avoid breathing its vapor. May be fatal if swallowed. If swallowed induce vomiting, contact a physician immediately.

Contains no silicone