



BRONCO RUST CONVERTER

PRODUCT DESCRIPTION:

Is an active pre-treatment solution intended to condition rusty steel surfaces. It converts the rust on the steel surface into a insoluble and stable salt of phosphoric acid, creating a grayish black color on the treated metal surface.

SUITABLE FOR:

- Roofs
- Trusses

APPLICATION:

Remove any loose or flaking rust with steel brush or grit 80 sand paper. Apply by nylon brush until rusty metal surface is fully wet. Allow to dry for 2 hours. Wipe off any residue with a dry cloth or scrub pad from the surface. Apply one to two coats Bronco Metal Primer before applying top coat paint, quick drying enamel or other solvent based paint.

COVERAGE:

25-30 m²/4liters @ 50 microns D.F.T.

SIZES AVAILABLE:

1 Liter & 4 Liters



PRECAUTION:

SPECIAL PRECAUTIONS: May cause eye and skin irritation. Harmful if swallowed. Exposure to mist, vapors or fumes should be minimized.

PERSONAL PROTECTION: When applying paint, it is advisable to wear safety glasses, long sleeves and gloves. Use adequate respirators as inhalation of mist may produce respiratory irritation.

VENTILATION: Keep containers tightly covered. Ensure good ventilation or use local exhaust if needed to control mist vapors.

HANDLING: During application of paint, do not eat, drink or smoke. Always wear personal protection. Wash thoroughly after handling.

STORAGE: Keep container closed when not in use. Store in a well ventilated room and avoid direct sunlight exposure. Empty product containers may contain product residue, avoid reusing of empty containers for other purposes. Container remains hazardous when empty. Continue to observe all precautions.