

PRIMERO PRO SUPER FINE SKIM COAT

PRODUCT DESCRIPTION:

Primero Pro Super Fine Skim Coat is a specially formulated, rapid-setting polymer modified coating, it is used to coat the imperfections and plaster the unevenness of the surface of walls, columns, beams and ceilings. It eliminates hairline cracks resulting to a smooth finish.

USES:

It is primarily used in interior wall and ceiling surfaces to fill and bridge cracks. It can be used to even out irregular surfaces of both interior and exterior concrete surfaces, plastered walls, and even ceilings. It is recommended for houses, schools, hospitals, offices, residential establishments and industrial and commercial buildings.

FEATURES and ADVANTAGES

- Hand or Machine Mix
- Long Pot Life
- Easy to Apply
- Excellent Coverage
- Covers Pinholes, Hairline Cracks, Surface Imperfections
- For new and old unpainted cement walls
- Sandable
- Can be applied in multiple coats

PACKAGING

20 Kg / Bag



MIXING: ADD 8 TO 8.5 LITERS OF CLEAN WATER. MIX WELL UNTIL THERE ARE NO LUMPS. LET STAND FOR 5 MINUTES BEFORE APPLYING ON WALL. PRODUCT HAS LONG POT LIFE. DO NOT ADD WATER

COVERAGE

1 to 1.1 kg per square meter per mm
20 kg bag will cover to 20 to 22 square meters @
1mm thickness

SURFACE PREPARATION

Ensure that surface is free from dirt, dust, oil and grease. Pre cast cement must be washed with soap and water to remove mold release agent.

For new and unpainted walls: wet surface with water until it has been absorbed. Wall should be damp with no drippings.

STORAGE

Keep dry. Keep away from direct sunlight. Avoid areas with high moisture levels.