



PRIMERO AGENT Q5 BOND

PRODUCT DESCRIPTION

Primero Agent Q5 Bond is a specially formulated acrylic based bonding agent to improve bonding and adhesion strength of tile adhesive or cement-sand screed. It increases flexural strength of medium and large tiles to reduce debonding of tiles.

USES

Bonding agent for walls and floor tiles, engineered stones, bricks, large and medium sized tiles, marble, granite and other natural stones.

SIZE AVAILABLE

4 liters

DIRECTION OF USE

SURFACE PREPARATION

Surface must be sound, clean, dry and free from dirt, dust, grease and oil. Ensure that surface is free from loose or flaking cement. Honeycombs must be hacked and filled with cement grout, plaster or fast-setting cement.

MIXING

Shake well before using.

APPLICATION

Using a pail or flat clean surface, add approximately 1 part water to 2 parts tile adhesive. (.75 to 1 liter water for every 2 kilos of tile adhesive) Mix well to make a thick mortar. Add 2 liters of Primero Agent Q5 Bond for every 20 to 25kg bag of tile adhesive for small to medium tiles. Mix well to achieve a creamy consistency. Apply to tiles in 3 to 5mm thickness.



For very large tiles (60cm x 60cm) and high traffic areas, add 4 liters to the same water and tile adhesive mixture as above. Mix well and apply tiles at thickness of 3 to 5mm using a notched trowel.

Firmly press tiles into position and allow to dry for 3 to 4 hours

PRECAUTIONS

- Do not take internally.
- Keep out of reach of children.
- Store in room temperature.
- Keep away from direct sunlight and sources of heat.
- Keep container closed when not in use.