

## > RESIN BASED SURFACE TREATMENT PRODUCTS



# PYE

PYE Products..... *easy to use*



## PYE WATER-LOCK

*The Waterproof Coating That Protects and Waterproof Masonry Surface*

### DESCRIPTION

**PYE WATER-LOCK** is an Acrylic Based Masonry Waterproofer which is used to solve water seepage problems. It is specially formulated to waterproof interior, exterior, below grade masonry walls, cinder and concrete blocks, stucco and brick, retaining walls, basement walls and foundations.

**PYE WATER-LOCK** has been tested under GB/T 23445 Hydrostatic Negative Pressure standard. Applied **PYE WATER-LOCK** is paintable over with good quality acrylic paint.

### DIRECTIONS FOR USE

#### **Surface preparation**

Surface must be clean and free from dirt, dust, grease, oil and paint. Patch evenly all holes or cracks and floor/ wall joints with **PYE AQUA PLUG** or fast setting hydraulic cement. Affected painted water-mark area must be removed by scrapping off or by using **PYE STRIPPA M**. The waterproofing performance of **PYE WATER-LOCK** is highly effective for unpainted surfaces. Not recommended for use on horizontal surface which are subject to foot traffic.

#### **Application**

Stir thoroughly before and during application. Do not thin. Paint only when air and surface is at room temperature or higher. Apply

**PYE WATER-LOCK** directly on bare masonry. Apply first coat with brush or good quality nylon bristle brush in order for **PYE WATER-LOCK** to penetrate into the pores of the masonry. Allow to dry 3 hours between coats. The second coat may be applied by brush or roller. 2 coats are sufficient depending on porosity of the surface/ substrate.

### TECHNICAL & PHYSICAL DATA

Colour	White
Form	Semi liquid paste
Adhesion	Adheres firmly to clean, dry and grease free concrete.
Odour	Slight odour, but odourless when dry.
Binder	Acrylic
Coverage	Approx. 1.5s.q. meter per kg for the first coat and up to 2.5s.q. meter per kg for succeeding coats.
Standards	Tested under GB/T 23445 Hydrostatic Negative Pressure standard.
Safety	Non flammable & non toxic.
Cleaning	Clean tools with water.

### PACKING

1.5kg, 4kg